Berridge Approved Materials Form

| ROOFING CONTRACTOR: | PROJECT NAME: |
|--|--|
| | |
| WARRANTY FILE #: | |
| | |
| PLEASE INDICATE WHICH PRODUCT(S) WILL BE USED AS ROOF UNDERLAYMENT AND SEALANT. | |
| ICE AND WATERSHIELD PRODUCTS | SEALANT |
| Use on curved roofs, low-sloped roofs, critical details, or per architectural specs. | ☐ Tremco Spectrum One |
| ☐ Mid-States Asphalt Quik-Stick HT Pro (60 mil)* | ☐ Dow 790 |
| ☐ Soprema Lastobond Shield HT (40 mil) | ☐ Pecora 890NST |
| ☐ MFM Ultra HT Wind & Water Seal (45 mil) | ☐ Duralink |
| ☐ Grace Ice & Watershield HT (40 mil) | ☐ Titebond Metal Roof Sealant |
| ☐ Grace Ice & Watershield (40 mil) | ☐ Triangle APS 500 |
| ☐ Grace Ultra (30 mil) | |
| ☐ Polyglass Polystick MTS Plus (60 mil) | UNDERLAYMENT |
| ☐ Polyglass Polystick MX | Only 30# felt with Berridge Felt caps is approved. |
| | |
| | |

FILL OUT AND PROMPTLY FAX OR EMAIL FORM TO:

BERRIDGE MANUFACTURING COMPANY | ATTN: WTW DEPARTMENT

FAX: 713-236-9422 | EMAIL: WTW@BERRIDGE.COM

Effective 4/21/2025



^{*} Please note, no other Mid-States Asphalt products with similar names or otherwise are approved for the Berridge Watertightness Warranty Program.