

# Berridge Coil & Flat Sheet

KYNAR 500® OR HYLAR 5000®



*Berridge Manufacturing Company offers premium coated metal coil and flat sheet material in steel and aluminum. Its robust exterior durability, thanks to full-strength Kynar 500® or Hylar 5000® resins, makes it ideal for architectural projects demanding long-lasting, high-performance finishes.*

*Whether used in residential, commercial, or industrial settings, Berridge's color finishes — with a 40-year guarantee against cracking, chipping, and peeling and a 30-year guarantee against fading and chalking\*\*\* — ensure a lasting,*

*vibrant appearance. These are the highest-quality exterior finishes available!*

*The availability of custom colors further allows architects and builders to tailor their coil and flat sheet metal to specific design requirements, making it a go-to choice for those seeking durability and design flexibility in their projects. Berridge takes pride in delivering high-quality products that combine durability with aesthetic appeal.*

## Materials

24 and 22 Gauge, Galvalume®\*  
0.032 and 0.040 Aluminum\*\*

## Specifications

- Grade 40, 40 ksi steel
- Finishes: Kynar 500® or Hylar 5000® Finish AZ-50 Galvalume®\* or Acrylic Coated AZ-55 Galvalume®\* (Unfinished)
- All Berridge coils are slit from either 42" or 48" master coils. Standard nominal coil widths are 14", 16", 21", and 24". Actual coil sizes are 13 7/8", 15 7/8", 20 7/8", and 23 7/8" respectively.
- Berridge can provide any custom coil width required from 48" and 42" master coils. Odd width slitting charge applies for non-standard sizes, and customer is responsible for any drop coils.
- Berridge standard and metallic color flat sheets are available in 48" or 42" widths by 120" in length.
- Pallet charges are waived for full pallet orders.
- Full pallets of 48" flats contain 60 sheets, and full pallets of 42" contain 100 sheets.
- Setup fee (per color) may apply if 1,750 square foot minimum order is not met.

## Installation

- Strippable plastic film is applied over all prefinished coils. This film must not be exposed to sun or moisture and must be removed prior to material installation.
- Stored material should be protected from the weather, well-ventilated and kept dry.
- Coils are wrapped in cardboard and banded eye-to-the-sky.
- Flat sheets are palletized and banded in corrugated steel and wooden pallets.

Note:

\* Galvalume® coating is an alloy composed of 55% aluminum and approx. 45% zinc by weight applied according to ASTM A792

\*\* 3105 or 3003 H14 Aluminum

\*\*\* See paint finish warranty samples at [www.berridge.com](http://www.berridge.com)



**CORPORATE HEADQUARTERS**

2610 Harry Wurzbach Road

San Antonio, TX 78209

(800) 669-0009

[www.Berridge.com](http://www.Berridge.com)