

# Berridge Product Application & Index

AVAILABLE IN ALL BERRIDGE COLORS

		ROOF SYSTEM	CURVED ROOF SYSTEM	WALL SYSTEM	CURVED WALL SYSTEM	SOFFIT SYSTEM	CEILING SYSTEM	FASCIA SYSTEM	SHEATHING SYSTEM	SCREEN WALL	FENCING SYSTEM	PAGE NUMBER
<b>STANDING SEAM SYSTEMS</b>	Tee-Panel	■	■					■				10
	High Seam Tee-Panel	■	■					■				12
	Tee-Lock Panel	■						■*				14
	Cee-Lock Panel	■						■				15
	Zee-Lock Panel	■	■					■				16
	Double-Lock Zee-Lock Panel	■						■*				18
<b>ALTERNATIVE SYSTEMS</b>	Batten Seam Panel	■						■				19
	Bermuda Panel	■						■				20
<b>SIMULATED TILE ROOF SYSTEMS</b>	Spanish Tile	■										21
	S-Tile	■										22
<b>SHINGLE SYSTEMS</b>	Fish Scale Shingle			■				■				23
	Victorian & Classic Shingles	■		■				■				24
<b>WALL, SOFFIT, CEILING AND FASCIA PANEL SYSTEMS</b>	HS-8 & HS-12 Panels			■		■	■		■	□		25
	HR-16 & HR-4 Panel			■			■		■	□		26
	HC-16 Panel			■		■	■		■	□		27
	BR-12 Panel			■			■		■	□		28
	Vee-Panel			□		■	■	■		□	□	29
	FW-1025 & FW-12 Panels			□		■	■	■		□		30
	L-Panel					■	■	■		□		31
	B-6 Panel			□	○	■	■	■		□	□	32
	Flush Seam Panel			□	○	■	■	■		□	□	33
	Thin-Line Panel			□	○	■	■	■		□	□	34
	Double Rib Panel	■										35
<b>EXPOSED FASTENER PANEL SYSTEMS</b>	Deep-Deck Panel	■		■		■	■	■	■	■		36
	S-Deck Panel	■	■	■	■	■	■	■	■	■		37
	"M" & "R" Panel	■		■		■	■	■	■	■		38
	Fluted Fascia			■				■				39
<b>SPECIALTY APPLICATION SYSTEMS</b>	Curved Flat Seam Panel							■				40

Please consult product pages and the BMC technical department for further details. Panel application can vary based on installation specifications. Please consult the BMC technical department concerning additional Watertightness Warranty installation requirements.

□ Vertical application only

○ Panel does not curve but can be installed on a curved wall

\* Requires flashing break from roof to fascia.