Berridge "R" Panel

EXPOSED FASTENER PANEL SYSTEM



The Berridge "R" Panel is a wide, economical panel providing 36" of coverage for vertical or horizontal applications.



24 and 22 Gauge Steel 0.032 Aluminum

Specifications

Uses: Roof, Wall, Soffit, Ceiling, Fascia, Mansard,

Sheathing, Screen Wall

Coverage: 36" Finishes: Smooth Fasteners: Exposed

Applications: Open framing or solid sheathing*

36" Coverage (914 mm) 1" (25 mm) 4" 4" 4" 12" (305 mm) 38 1/4" Actual Width (972 mm)

Installation

- Panel is available from the factory in continuous lengths to a maximum of 40.
- Structural properties allow it to be utilized as a sheathing option
- Estimate 115 fasteners/sq.
- Use inside and outside foam closures to help prevent air infiltration at ridges, eaves, head walls, etc.
- Use expandable foam filler tape per installation details at closure at hips and valleys.
- Use mastic sealant tape per installation details at panel endlaps, sidelaps, skylights, with foam closure, etc.

Note: Unless otherwise noted, all testing is for steel only.

Vertical or horizontal for wall applications.

Pictured Above and Right
Project: Liberty Christian School
Architect: FJLC & Associates
General Contractor: Joeris
General Contractors
Installing Contractor: Roof
Management Services, Inc.
Color: Sierra Tan



BERRIDGE "R" PANEL TESTING AND CERTIFICATION SUMMARY CHART

CATEGORY		CHARACTERISTIC	TEST METHOD	PURPOSE	RESULT
FIRE		Room Fire Performance	UL 790	Test methods for fire tests of roof coverings	Class A Rating
ENVIRONMENTAL	-	Impact Resistance	UL 2218	Impact resistance of prepared roof coverings	Class 4 Rating
PRODUCT LISTINGS	•	Florida Product Approval	TAS 125	Local and state approval of products and systems for compliance with the structural requirements of the Florida Building Code	FL# 14210.7 (24 GA-Purlins) FL# 14669.5 (24 GA-Girts)
	•	Underwriters Laboratories	UL 580 Uplift Class 90	Standard for Tests for Uplift Resistance of Roof Assemblies	Construction No. 79 (24 GA - Purlins) Construction No. 161 (24 GA - Purlins) Construction No. 30 (24 GA - Purlins)
■ - Steel only □ - Steel and Aluminum					

■ - Steel only □ - Steel and Aluminum
For further details please visit www.berridge.com