

COIL & COVERAGE

Coil Size: 13-7/8" (Nominal 14")

Coil Quantity: 109.80 SF per SQ of coverage


SYSTEM ACCESSORIES (Factory Formed)

Seam Caps: 94.12LF per SQ of coverage

Tee-Clips: 80 clips/SQ (typically at 20" o.c.)

***Folding Tee-Clips:** 80 clips/SQ (for curved panels)

MINIMUM CURVING RADII (Consult BMC for smaller radii)



Convex: 4'



Concave: 6'

SALE & LEASING INFORMATION

Sale Price: Consult BMC

Non-Licensee Lease: Consult BMC

Licensee Lease: Consult BMC

Long Term Lease: Consult BMC

SPECIFICATIONS

Mounted on heavy duty 4-wheel table

Width: 35" **Length:** 88" **Height:** 53"

Weight: 1470 lbs with shipping cover

1. 2 HP electric motor - 110V single-phase current
2. High Speed - 45' per minute
3. Built-in uncoiler (up to 2000 lb coil)
4. Stainless steel heat-treated, hardened rollers
5. Unique side production for ease of operation
6. Mechanical slitter shear
7. Accurate-length gauge (computer optional)
8. Continuous-length panels, based on coil size
9. All sealed bearings
10. Coil handling apparatus included
11. Curves panels and seam caps

NOTES

1. * Folding Tee-Clips are 28 gauge material



The Berridge Model SS-14 Portable Roll-Former forms continuous-length, eave-to-ridge straight Berridge Tee-Panels, and by hand-adjusting the last roll, also forms Curved Tee-Panels. The Berridge Model SS-14 Portable Roll Former also curves the factory-formed seam caps. Individual factory formed Tee-Clips are used with straight panels and 28-gauge Folding Tee-Clips are used with curved panels. Refer to www.berridge.com for ASTM & UL Ratings.

