Berridge Thin-Line Panel

WALL, SOFFIT, CEILING AND FASCIA PANEL SYSTEM



Materials

24 Gauge Steel

Specifications

Uses: Wall, Soffit, Ceiling, Fascia, Screen Wall, Berridge Fencing System Coverage: 3 %" Finishes: Smooth, woodgrain embossed, or stucco embossed Fasteners: Concealed Applications: Vertical over open framing or solid sheathing

Installation

- Panel is available from the factory in continuous lengths up to a maximum of 40'.
- Panel includes a channel drain interlock.
- May be site formed in continuous lengths with the Berridge TL-6 Roll Former.

Pictured Above Project: Artisan Cove Live-Work - Austin, TX General Contractor: SpawGlass Installing Contractor: Architecture Roof Systems, LLC Colors: Charcoal Grey, Deep Red, Royal Blue, Teal Green, Bristol Blue, Colonial Red, Evergreen, Patina Green, Terra-Cotta, Zinc Grey





Pictured Above Project: Scottsdale Crossing - AZ Architect: Nelsen Partners General Contractor: Whiting Turner Installing Contractor: Total Metals Color: Zinc-Cote™

All information subject to change without notice. See website for details, specifications and Watertightness Warranty requirements. © Berridge Manufacturing Company 2024 • (800) 669-0009 • www.Berridge.com

BERRIDGE THIN-LINE PANEL TESTING AND CERTIFICATION SUMMARY CHART

CATEGORY		CHARACTERISTIC	TEST METHOD	PURPOSE	RESULT
PERFORMANCE	-	Uplift Resistance	ASTM E-330	Test method to determine structural performance under uniform static air pressure	See Load Chart on Berridge website
PRODUCT Listings	-	Florida Product Approval	TAS 202	Local and state approval of products and systems for compliance with the structural requirements of the Florida Building Code	FL# 14669.7 (24 GA - Steel Girts)

■ - Steel only □ - Steel and Aluminum For further details please visit www.berridge.com



CORPORATE HEADQUARTERS 2610 Harry Wurzbach Road San Antonio, TX 78209 (800) 669-0009 www.Berridge.com